

## Vermeer VSK100D

- Engine: 25 hp (18.6 kw) Kubota diesel (21 hp SAE net)
- Blower: 575 (16.3 m<sup>3</sup>/min.) CFM Lobe type with dual splash oil lubrication
- Filtration: 3-Stage with cyclone separator & 2-micron poly filter
- Controls: electric start, electric throttle, full spoil tank override, water pump clutch, automatic throttle
- Door type: full open
- Maximum vacuum: 15" Hg (381 mm Hg)
- Water tank: 50 gal (189 L)
- Vacuum hose: 16' (4.8 m) of 3" (7.6 cm)
- Fuel tank: 6 gal (22.7 L)
- Gauges: fuel level, hour meter, vacuum, water pressure
- Spoil tank: 100 gal (379 L)
- Tank lift type: fixed 45-degree angle
- Full tank shut off: electronic float
- Water pump: 4.0 GPM @ 3000 PSI (15.1 LPM @ 206.9 BAR)
- Low water shut off: electronic
- Skid: 121" (254 cm) (L) x 48" (122 cm) (W) x 63" (160 cm) (H)
- Skid Maximum weight: 2,800 lb. (1027 kg)
- Skid dry weight: 1,400 lb. (635 kg)
- Enclosure lockable sound dampening

